

> s vestanat t 1890/cn
1 VESTANAT T 1890/CN

> d

ANSWER 1 OF 1 REGISTRY COPYRIGHT 2004 ACS on STN

73666-46-3 REGISTRY

Vestanat T 1890 (9CI) (CA INDEX NAME)

OTHER NAMES:

IPDI-T 1890

T 1890

Vestanat IPDI-T 1890

82197-86-2

NOTE An isophorone diisocyanate-based isocyanurate-containing adduct (Huls AG)

Unspecified

COM, MAN

C STN Files: CA, CAPLUS, PROMT, TOXCENTER, USPATFULL

*** STRUCTURE DIAGRAM IS NOT AVAILABLE ***

92 REFERENCES IN FILE CA (1907 TO DATE)

63 REFERENCES TO NON-SPECIFIC DERIVATIVES IN FILE CA

92 REFERENCES IN FILE CAPLUS (1907 TO DATE)

> s tolonate/cn
0 TOLONATE/CN

> file caplus

COST IN U.S. DOLLARS

SINCE FILE

TOTAL

ENTRY

SESSION

ULL ESTIMATED COST

16.32

16.53

FILE 'CAPLUS' ENTERED AT 14:08:07 ON 07 APR 2004

SE IS SUBJECT TO THE TERMS OF YOUR STN CUSTOMER AGREEMENT.

PLEASE SEE "HELP USAGETERMS" FOR DETAILS.

COPYRIGHT (C) 2004 AMERICAN CHEMICAL SOCIETY (ACS)

copyright of the articles to which records in this database refer is
held by the publishers listed in the PUBLISHER (PB) field (available
for records published or updated in Chemical Abstracts after December
5, 1996), unless otherwise indicated in the original publications.
The CA Lexicon is the copyrighted intellectual property of the
American Chemical Society and is provided to assist you in searching
databases on STN. Any dissemination, distribution, copying, or storing
of this information, without the prior written consent of CAS, is
strictly prohibited.

FILE COVERS 1907 - 7 Apr 2004 VOL 140 ISS 15

FILE LAST UPDATED: 6 Apr 2004 (20040406/ED)

This file contains CAS Registry Numbers for easy and accurate
substance identification.

> s l1 or l2 or l3

0 L1

92 L2

0 L3

4 92 L1 OR L2 OR L3

> s l4 and (fluor? or perfluoro?)

1002394 FLUOR?

44645 PERFLUORO?

5 9 L4 AND (FLUOR? OR PERFLUORO?)

> s l5 and (oil repellant or water repellant)

675471 OIL

1039 REPELLANT
76 OIL REPELLANT
(OIL (W) REPELLANT)
2119349 WATER
1039 REPELLANT
521 WATER REPELLANT
(WATER (W) REPELLANT)
0 L5 AND (OIL REPELLANT OR WATER REPELLANT)

> s 15 and oligourethane? or polyurethane?
541 OLIGOURETHANE?
123992 POLYURETHANE?
123992 L5 AND OLIGOURETHANE? OR POLYURETHANE?

> s 17 and (fluor? or perfluoro?)
1002394 FLUOR?
44645 PERFLUORO?
7915 L7 AND (FLUOR? OR PERFLUORO?)

> s 18 and (oil repellent or water repellent)
675471 OIL
1039 REPELLANT
76 OIL REPELLANT
(OIL (W) REPELLANT)
2119349 WATER
1039 REPELLANT
521 WATER REPELLANT
(WATER (W) REPELLANT)
7 L8 AND (OIL REPELLANT OR WATER REPELLANT)

> s 15 or 19
16 L5 OR L9

> s 110 and py<1999
18918812 PY<1999
10 L10 AND PY<1999

> d 1-10 ibib abs hitstr

11 ANSWER 1 OF 10 CAPLUS COPYRIGHT 2004 ACS on STN
ACCESSION NUMBER: 2003:734648 CAPLUS
DOCUMENT NUMBER: 139:246986
TITLE: Coatings based on **perfluoropolyethers** and
use with good stain release
INVENTOR(S): Marchetti, Roberta; Malavasi, Massimo
PATENT ASSIGNEE(S): Solvay Solexis S.p.A., Italy
SOURCE: Eur. Pat. Appl., 22 pp.
CODEN: EPXXDW
DOCUMENT TYPE: Patent
LANGUAGE: English
FAMILY ACC. NUM. COUNT: 2
PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
EP 1344807	A2	20030917	EP 2003-6993	19970609
EP 1344807	A3	20040114		
R: AT, BE, CH, DE, DK, ES, FR, GB, IT, LI, NL, SE, FI				
EP 812891	A2	19971217	EP 1997-109298	19970609 <--
EP 812891	A3	19981118		
EP 812891	B1	20031001		
R: AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LI, LU, NL, SE, MC, PT, IE, FI				

PRIORITY APPLN. INFO.: IT 1996-MI1178 A 19960610
EP 1997-109298 A3 19970609

3 The title coating compns. comprise (A) 10-60% of (1) a (per) **fluoropolyether** prepolymer having a polyisocyanate functionality obtained by reacting a **fluoropolyethers** having ≥ 2 hydroxy groups, optionally containing monofunctional (per) **fluoropolyether**,

with isocyanurate ring-containing polyisocyanate, preferably obtained by cyclotrimerization of HDI, IPDI or other monomeric diisocyanates and/or (2) non-**fluorinated** isocyanurate-containing polyisocyanates and/or hydrogenated polyisocyanate prepolymers, (B) 0.1-50% of a hydroxy-containing (per)**fluoropolyether** as in (A) but having a lower pre-polymerization degree, and (C) 10-90% diluting solvent.

73666-46-3DP, Vestanat T 1890, reaction products with hydroxy-terminated **perfluoro** polyethers

RL: IMF (Industrial manufacture); POF (Polymer in formulation); TEM (Technical or engineered material use); PREP (Preparation); USES (Uses) (**perfluoropolyether**-based coatings with hardness, chemical resistance, stain release property and long pot life)

73666-46-3 CAPLUS

Vestanat T 1890 (9CI) (CA INDEX NAME)

*** STRUCTURE DIAGRAM IS NOT AVAILABLE ***

11 ANSWER 2 OF 10 CAPLUS COPYRIGHT 2004 ACS on STN

ACCESSION NUMBER: 1998:13718 CAPLUS

DOCUMENT NUMBER: 128:62936

TITLE: **Perfluoropolyether**-based protective coatings

INVENTOR(S): Marchetti, Roberta; Malavasi, Massimo

PATENT ASSIGNEE(S): Ausimont S.P.A., Italy

SOURCE: Eur. Pat. Appl., 26 pp.

CODEN: EPXXDW

DOCUMENT TYPE: Patent

LANGUAGE: English

FAMILY ACC. NUM. COUNT: 2

PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
EP 812891	A2	19971217	EP 1997-109298	19970609 <--
EP 812891	A3	19981118		
EP 812891	B1	20031001		
R: AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LI, LU, NL, SE, MC, PT, IE, FI				
EP 1344807	A2	20030917	EP 2003-6993	19970609
EP 1344807	A3	20040114		
R: AT, BE, CH, DE, DK, ES, FR, GB, IT, LI, NL, SE, FI				
AT 251207	E	20031015	AT 1997-109298	19970609
CA 2207481	AA	19971210	CA 1997-2207481	19970610 <--
JP 10072568	A2	19980317	JP 1997-152637	19970610 <--
US 6071564	A	20000606	US 1997-872454	19970610

PRIORITY APPLN. INFO.: IT 1996-MI1178 A 19960610
EP 1997-109298 A3 19970609

B Protective coating compns. comprise (A) 10-60 weight% of (1) a (per) **fluoropolyether** prepolymer having a polyisocyanic functionality obtainable by reacting a **fluoropolyethers** having ≥ 2 hydroxy groups with a isocyanurate ring-containing polyisocyanate, preferably obtained by cyclotrimerization of HDI, IPDI or other monomeric diisocyanates and/or (2) non-**fluorinated** isocyanurate-containing polyisocyanates and/or hydrogenated polyisocyanate prepolymers, (B) 0.1-50 weight% of a hydroxy-containing (per)**fluoropolyether** as defined in (A) but having a lower pre-polymerization degree, and (C) 10-90 weight%, with respect to the resin of a diluting solvent.

73666-46-3DP, Vestanat T 1890, reaction products with hydroxy-terminated **perfluoro** polyethers

RL: IMF (Industrial manufacture); POF (Polymer in formulation); TEM (Technical or engineered material use); PREP (Preparation); USES (Uses) (**perfluoropolyether**-based protective coatings)

73666-46-3 CAPLUS

Vestanat T 1890 (9CI) (CA INDEX NAME)

*** STRUCTURE DIAGRAM IS NOT AVAILABLE ***

11 ANSWER 3 OF 10 CAPLUS COPYRIGHT 2004 ACS on STN

ACCESSION NUMBER: 1995:867592 CAPLUS

DOCUMENT NUMBER: 123:259184

TITLE: Multilayered plastic pipe with **fluoropolymer**
and polyamide layers
INVENTOR(S): Roeber, Stefan; Jadamus, Hans; Boer, Michael;
Feinauer, Roland; Herrmann, Hans-Dieter; Ries, Hans
PATENT ASSIGNEE(S): Huels A.-G., Germany
SOURCE: Eur. Pat. Appl., 17 pp.
CODEN: EPXXDW
DOCUMENT TYPE: Patent
LANGUAGE: German
FAMILY ACC. NUM. COUNT: 1
PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
EP 650004	A1	19950426	EP 1994-100431	19940113 <--
R: CH, DE, ES, FR, GB, IT, LI, NL, SE				
DE 4336289	A1	19950427	DE 1993-4336289	19931025 <--
JP 07117189	A2	19950509	JP 1994-7640	19940127 <--
JP 07090628	B4	19951004		

PRIORITY APPLN. INFO.: DE 1993-4336289 19931025
B The title pipe comprises, in turn, an outer layer of a polyamide (e.g., nylon 12), a layer of a mixture of a linear crystalline polyester [e.g., poly(butylene terephthalate)] and a compound containing ≥ 2 isocyanate groups (e.g., isophorone diisocyanate or a derivative), a polyamide layer, a layer of a mixture of a polyamide and a polymer of an (alkyl)acrylic acid ester, and an inner layer of poly(vinylidene **fluoride**). The pipe shows good interlayer adhesion, mech. properties, and chemical resistance and is especially useful for transporting petrochems. such as MeOH-containing fuels.

T **73666-46-3D**, Vestanat T 1890, derivs., reaction products with polyesters

RL: PRP (Properties); TEM (Technical or engineered material use); USES (Uses)

(in laminated pipe with **fluoropolymer** lining for transport of methanol-containing fuels and petrochems.)

N 73666-46-3 CAPLUS
N Vestanat T 1890 (9CI) (CA INDEX NAME)

*** STRUCTURE DIAGRAM IS NOT AVAILABLE ***

11 ANSWER 4 OF 10 CAPLUS COPYRIGHT 2004 ACS on STN

ACCESSION NUMBER: 1995:758621 CAPLUS

DOCUMENT NUMBER: 123:144917

TITLE: Microemulsion polymerization systems, containing organic polymers with pendant **fluoralkyl** groups, and coating materials prepared from them

INVENTOR(S): Wu, Huey Shen; Kaler, Eric W.

PATENT ASSIGNEE(S): W. L. Gore and Associates, Inc., USA

SOURCE: PCT Int. Appl., 21 pp.

CODEN: PIXXD2

DOCUMENT TYPE: Patent

LANGUAGE: English

FAMILY ACC. NUM. COUNT: 3

PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
WO 9422928	A1	19941013	WO 1993-US8884	19930920 <--
W: AT, AU, BB, BG, BR, BY, CA, CH, CZ, DE, DK, ES, FI, GB, HU, JP, KP, KR, KZ, LK, LU, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SK, UA, VN				
RW: AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE				
CA 2156527	AA	19941013	CA 1993-2156527	19930920 <--
CA 2156527	C	19990112		
AU 9349306	A1	19941024	AU 1993-49306	19930920 <--
AU 681598	B2	19970904		
EP 690881	A1	19960110	EP 1993-921691	19930920 <--
EP 690881	B1	19990421		
R: AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LI, LU, MC, NL, PT, SE				

GB 2291063	A1	19960117	GB 1995-19422	19930920 <--
GB 2291063	B2	19971105		
HU 72424	A2	19960429	HU 1995-2408	19930920 <--
HU 216325	B	19990628		
DE 4397309	T	19960627	DE 1993-4397309	19930920 <--
EP 856262	A1	19980805	EP 1998-105006	19930920 <--
R: AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LI, LU, NL, SE, MC, PT, IE				
AT 179187	E	19990515	AT 1993-921691	19930920
US 5385694	A	19950131	US 1994-220323	19940330 <--
US 5539047	A	19960723	US 1994-227862	19940414 <--
SE 9503228	A	19950918	SE 1995-3228	19950918 <--
SE 514801	C2	20010423		
AU 9746883	A1	19980212	AU 1997-46883	19971204 <--
AU 714262	B2	19991223		

PRIORITY APPLN. INFO.:

US 1993-38573	A	19930326
EP 1993-921691	A3	19930920
WO 1993-US8884	W	19930920

8 An aqueous latex (average particle diameter 0.01-0.5 μ) consists of particles of an organic polymer having pendant **fluorinated** (especially **fluoroalkyl**) organic side chains and is prepared by microemulsion polymerization. Suitable polymers are those derived from **fluoroalkyl** acrylates, methacrylates, aryl urethanes, allyl urethanes, maleate esters, urethane acrylates, acrylamides, and sulfonamide acrylates. Especially suitable are polymers derived from a (meth)acrylate monomer of general formula $CF_3(CF_2)_nCH_2CH_2OC(O)CR:CH_2$ (R = H or Me, n = 3-13). The latex typically contains an unsatd. **fluoroalkyl** group-containing monomer and a surfactant of general formula R_fRYX (R_f is C1-15-**fluoroalkyl** or **fluoroalkyl** ether; R = C \leq 4-alkylene or alkylene thioether; Y is carboxylate, sulfonate, sulfate, or hydroxyl; and X is alkali metal, NH_4 , or oxyethylene quaternary ammonium ions). The latex is suitable for coating of porous substrates (i.e., for forming **oil-repellant** surfaces).

1 ANSWER 5 OF 10 CAPLUS COPYRIGHT 2004 ACS on STN

ACCESSION NUMBER: 1994:411922 CAPLUS

DOCUMENT NUMBER: 121:11922

TITLE: Acrylic-**fluoropolymer**-siloxane coating compositions

INVENTOR(S): Miyazaki, Nobuyuki; Takayanagi, Takashi; Hashimoto, Toshihiko; Momotori, Hiroshi; Kondo, Masami; Sakai, Yoshihiko

PATENT ASSIGNEE(S): Asahi Glass Co Ltd, Japan; Asia Ind Co Ltd

SOURCE: Jpn. Kokai Tokkyo Koho, 6 pp.

CODEN: JKXXAF

DOCUMENT TYPE: Patent

LANGUAGE: Japanese

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
JP 06016992	A2	19940125	JP 1992-200681	19920703 <--
PRIORITY APPLN. INFO.:			JP 1992-200681	19920703

8 Title compns. for outdoor exposed substrates showing improved weatherability contain 100 parts solvent-soluble polymers (A) containing $\geq 10\%$ F derived from **fluoroolefin** units including crosslinkable sites, 1-80 parts acrylic polyols having glass transition temperature (T) $\geq 80^\circ$, 1-300 parts silicone oligomers having T $\geq 50^\circ$, 1-40 parts crosslinking agents forming linkage with the sites described in A, and 1-40 parts crosslinking agents having T $\geq 50^\circ$ forming linkage with the described sites in A. Thus, 100 parts 60:18:15:10 chlorotrifluoroethylene-cyclohexyl vinyl ether-Et vinyl ether-hydroxybutyl vinyl ether copolymer, 20 parts 51%-solids 40:50 2-hydroxyethyl methacrylate-Me methacrylate copolymer (T 82°), 10 parts γ -methacryloxypropyltrimethoxysilane homopolymer (T 120°), 12 parts C-HX (HDI cyclic trimer), and 12 parts IPDI-T1890 (T $\geq 50^\circ$), and xylene were mixed to give a white coating, which was applied onto an Al plate and exposed outdoor for 3 mo to show retention of lightness.

73666-46-3, Vestanat T 1890
RL: MOA (Modifier or additive use); USES (Uses)
(crosslinking agents, for acrylic **fluoropolymer**-siloxanes,
for coatings, with weatherability)
73666-46-3 CAPLUS
Vestanat T 1890 (9CI) (CA INDEX NAME)

*** STRUCTURE DIAGRAM IS NOT AVAILABLE ***

1 ANSWER 6 OF 10 CAPLUS COPYRIGHT 2004 ACS on STN
ACCESSION NUMBER: 1993:582819 CAPLUS
DOCUMENT NUMBER: 119:182819
TITLE: Isocyanate derivatives comprising
fluorochemical oligomers for treating fibrous
substrates
INVENTOR(S): Dams, Rudolf J.; De Witte, Johan E.
PATENT ASSIGNEE(S): Minnesota Mining and Manufacturing Co., USA
SOURCE: PCT Int. Appl., 126 pp.
CODEN: PIXXD2
DOCUMENT TYPE: Patent
LANGUAGE: English
FAMILY ACC. NUM. COUNT: 1
PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
WO 9217635	A1	19921015	WO 1992-US978	19920204 <--
W: BR, CA, JP, KR				
RW: AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LU, MC, NL, SE				
US 5276175	A	19940104	US 1991-679633	19910402 <--
CA 2105301	AA	19921003	CA 1992-2105301	19920204 <--
EP 578651	A1	19940119	EP 1992-906091	19920204 <--
EP 578651	B1	19950913		
R: AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LI, LU, MC, NL, SE				
JP 06506239	T2	19940714	JP 1992-506302	19920204 <--
JP 3242920	B2	20011225		
BR 9205842	A	19940802	BR 1992-5842	19920204 <--
US 5453540	A	19950926	US 1993-158203	19931129 <--
PRIORITY APPLN. INFO.:				
				US 1991-679633 A 19910402
				WO 1992-US978 W 19920204

Compds. are prepared which comprise a F-containing oligomeric portion, an organic moiety, and a group which can impart a soft hand, stain release, water repellency, or a durable property when the compound is applied to a fibrous substrate, the oligomeric portion being bonded to the organic moiety by an isocyanate-derived linking group. A 2-mercaptoethanol end-capped N-methylperfluorooctanesulfonamidoethyl acrylate homopolymer was reacted with PAPI, and free isocyanate groups were blocked with 2-butanone oxime to give a compound which was emulsified and padded with a resin composition on cotton to give an oil-repellent finish showing good wash fastness.

73666-46-3D, IPDI-T 1890, reaction products with
fluoropolymers
RL: USES (Uses)
(water- and oil-proofing compns. containing, for textiles)
73666-46-3 CAPLUS
Vestanat T 1890 (9CI) (CA INDEX NAME)

* STRUCTURE DIAGRAM IS NOT AVAILABLE ***

1 ANSWER 7 OF 10 CAPLUS COPYRIGHT 2004 ACS on STN
ACCESSION NUMBER: 1987:139917 CAPLUS
DOCUMENT NUMBER: 106:139917
TITLE: Clear, weather-resistant silicone coating compositions
for metallized plastics
INVENTOR(S): Penn, Howard I.
PATENT ASSIGNEE(S): Morton Thiokol, Inc., USA
SOURCE: U.S., 8 pp.
CODEN: USXXAM
DOCUMENT TYPE: Patent
LANGUAGE: English

FAMILY ACC. NUM. COUNT: 1
PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
US 4640868	A	19870203	US 1986-828468	19860210 <--
AU 8767424	A1	19870813	AU 1987-67424	19870108 <--
AU 583700	B2	19890504		
EP 232971	A2	19870819	EP 1987-300216	19870112 <--
EP 232971	A3	19900321		
R: DE, FR, GB, IT, NL, SE				
NO 8700376	A	19870811	NO 1987-376	19870129 <--
CA 1279144	A1	19910115	CA 1987-529058	19870205 <--
DK 8700643	A	19870811	DK 1987-643	19870209 <--
JP 62185764	A2	19870814	JP 1987-27982	19870209 <--
JP 03075582	B4	19911202		
BR 8700576	A	19871208	BR 1987-576	19870209 <--
PRIORITY APPLN. INFO.:		US 1986-828468		19860210

3 Title composition comprises the hydrolyzed reaction product of an isocyanurate with an aminodisilane compound. Reaction of 130 g Desmodur N3300 with 228 g silane Y 9492 (aminodisilane) in the presence of Bu₂Sn(OAc)₂ at 85° for 2 h gave a clear to light yellow liquid, diluted in MEK and EtOH, hydrolyzed by action of AcOH, heated 3 h at 46° to give a product of which 100 parts was diluted in 10 parts 2% Bu₂Sn(OAc)₂ in PhMe to give the coating. The coating was applied to aluminized polyester film and dried 1 min at 125° to give a 2.5 μ coating showing no moving of the surface in heat, solvent, and water resistance tests.

73666-46-3D, adducts with aminoalkoxysilanes, hydrolyzed

RL: TEM (Technical or engineered material use); USES (Uses)
(coatings, moisture-curable, weatherable, for metalized plastics)

73666-46-3 CAPLUS

Vestanat T 1890 (9CI) (CA INDEX NAME)

** STRUCTURE DIAGRAM IS NOT AVAILABLE **

11 ANSWER 8 OF 10 CAPLUS COPYRIGHT 2004 ACS on STN

ACCESSION NUMBER: 1974:72043 CAPLUS

DOCUMENT NUMBER: 80:72043

TITLE: Polymeric composition for the production of wear-resistant garments

INVENTOR(S): Aldrich, William E.

PATENT ASSIGNEE(S): Warnaco Inc.

SOURCE: U.S., 3 pp.
CODEN: USXXAM

DOCUMENT TYPE: Patent

LANGUAGE: English

FAMILY ACC. NUM. COUNT: 1

PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
US 3763078	A	19731002	US 1970-93804	19701130 <--
PRIORITY APPLN. INFO.:		US 1970-93804		19701130

3 A nonaq. solution of a **polyurethane** and a **fluorocarbon oil repellent** and soil release agent was sprayed onto shirt collars and neckbands and polymerized in sites by heating under pressure to give improved wear and soil resistance. A PhMe-iso-PrOH solution of a 1,6-hexamethylene diisocyanate-castor oil prepolymer and Scotchgard FC 218 [50641-94-6] was sprayed onto collars of 65:35% polyester-cotton shirts. After pressing 12 sec at 360.deg.F and 15 psi the shirts with stood 12-20 wearing and laundering cycles without pilling or staining compared to 3-10 cycles for untreated shirts.

11 ANSWER 9 OF 10 CAPLUS COPYRIGHT 2004 ACS on STN

ACCESSION NUMBER: 1972:87057 CAPLUS

DOCUMENT NUMBER: 76:87057

TITLE: **Fluorinated-nonfluorinated polymer mixtures** for wool finishing

AUTHOR(S): Ellison, A. H.; Margeson, J. H.; Galligan, J. D.;

CORPORATE SOURCE: Schwartz, A. M.; Pittman, A. G.; Wasley, W. L.
SOURCE: Gillette Co. Res. Inst., Rockville, MD, USA
Applied Polymer Symposia (1971), No. 18(Pt.
1), 579-84
CODEN: APPSBX; ISSN: 0570-4898
DOCUMENT TYPE: Journal
LANGUAGE: English
B Mixts. containing Adiprene L-100 and poly(1H,1H-pentadecafluorooctyl acrylate)
[26337-50-8] or a polymer prepared by hydrolytic polycondensation of
3-(heptafluoroisopropoxy)propyltrichlorosilane [15538-93-9] gave wool
fiber shrinkage control finishes with oil repellancy that was not fast to
laundering.

11 ANSWER 10 OF 10 CAPLUS COPYRIGHT 2004 ACS on STN
ACCESSION NUMBER: 1971:450369 CAPLUS
DOCUMENT NUMBER: 75:50369
TITLE: **Fluorohydrocarbon**-containing polymers for
making textiles, paper, and leather, oil- and
water-repellant
INVENTOR(S): Monaco, Luigi L.; Guerrato, Alfredo; Fabbro, Dario;
Donadello, Graziello
PATENT ASSIGNEE(S): Rimar S.p.A.
SOURCE: Ger. Offen., 63 pp.
CODEN: GWXXBX
DOCUMENT TYPE: Patent
LANGUAGE: German
FAMILY ACC. NUM. COUNT: 1
PATENT INFORMATION:

PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
DE 2018365		19710422		
FR 2043347			FR	
GB 1310823			GB	
US 3671493		19720000	US	
PRIORITY APPLN. INFO.:		IT		19690416
		IT		19690606

B Water-and oil-repellant agents for textiles, paper and
leather were prepared from polymers containing **perfluoroalkyl** groups.
Thus, Et **perfluorooctanoate** was condensed with aziridine at
 $\leq 5^\circ$. The resulting polymer was dissolved in
Me₂CO-CCl₂FCF₂Cl (50:50 by volume) and added dropwise to boiling
polyurethane prepolymer (from 1,1,1-trimethylolpropane, propylene
oxide and hexamethylene diisocyanate) in CCl₂FCF₂Cl. A solution of the
resulting polymer in CCl₄ was used to impart water- and oil-resistance to
woven wool fabric.